

TECHNICAL DATA SHEET

HiNEL® Plus- TWINDET



Description

HiNEL® Plus TWINDET is a non-electric detonator assembly consisting of a combination of a surface delay connection detonator(SDD) and a down hole delay detonator(DHD) with a consistent and accurate delay time. HiNEL® Plus TWINDET assemblies are designed for use in both open pit and underground mines. The shock tube is both abrasion resistant and high-strength and transmits the signal to detonator in order to initiate. Each end of shock tube is crimped into the detonators, and the surface detonator shell is enclosed in a connector block. Labels showing the lengths and delay times are attached on the shock tube.



Features & Benefits

The surface detonator consists of a non-electric detonator containing a delay element, a low strength Di-azo Di-Nitro Phenol (DDNP) base charge and a color-coded connector block to optimally deliver effective blasting signals whilst minimizing damages to the connectors and preventing cut-offs.

The downhole detonator consists of a non-electric detonator containing a delay element and a high strength Pentaerythritol Tetranitrate (PETN) base charge.

By adopting a 3 layer shock tube, rubber plug and triple crimping, HiNEL® Plus TWINDET Series also have enhanced tensile strength.

Usage Instructions

HiNEL® Plus TWINDET detonators enable an unlimited number of blast holes to be fired sequentially, where a constant inter-hole delay is desired. Using the “clip and slide” technique, clip each shock tube individually into connector block, ensuring that connector and the tubes are kept at right angles and there is no crossover nor tubes that lie within 300mm of connector block. HiNEL® Plus TWINDET detonators will initiate up to six standard 3.0mm shock tubes in both directions.

The downhole detonator of a HiNEL® Plus TWINDET detonator assembly should be fully enclosed within a suitable booster or primer and never be placed inside blast holes or charging hoses directly. If used inside blast holes, HiNEL® Plus TWINDET detonators should be reversed primed ensuring the downhole detonator base is pointing towards the blast hole collar.

Excessive force should not be used when handling shock tubes connected to detonators or primers. A replacement should be used if a primer becomes stuck or non-retrievable.

HiNEL® Plus TWINDET detonators are made up of a 3 layer shock tube and have enhanced tensile strength, however moisture may become present if the tubing is split or cut in any way, and this may result in a misfire. HiNEL® Plus TWINDET shock tube and connector should be protected from impact or damage. Misfires may occur if shock tube is damaged or cut. The surface detonator is not suitable for initiating detonating cord.

Recommended Sleep time of HiNEL® Plus TWINDET detonators is 2 weeks at temperatures below 40°C. Sleep time capability may be reduced at temperatures above 40°C.

Technical Data

HiNEL® Plus TWINDET		
Base Charge	DHD	PETN, #8 (730mg)
	SDD	DDNP (200mg)
Primary Charge	DHD	DDNP
Shell	Aluminum	
Outer Diameter of Shell (mm)	7.5	
Outer Diameter of Shock Tube (mm)	3.0	
Length of Shell (mm)	DHD	From 80 to 90
	SDD	59
Tensile Strength of Shock Tube	Nominal 45 kgf	
Length of Shock Tube (m)	2.4 / 3.6 / 4.8 / 6.0 / 7.2 / 9.0 / 12.0 / 15.0 / 18.0 / 21.0 / 24.0 / 30.0 / 36.0 (Custom made possible)	

HiNEL® Plus- TWINDET

Revised on: July 9th, 2020 (Ver 1.4)

www.hanwhacorp.co.kr/eng/explosives

TECHNICAL DATA SHEET

HiNEL® Plus- TWINDET



Standard Delay Range

Delay Time (ms)	Color of Shock Tube
400 (DHD)	-
425 (DHD)	
450 (DHD)	
475 (DHD)	
500 (DHD)	
550 (DHD)	
600 (DHD)	
650 (DHD)	
0 (SDD)	
17 (SDD)	Yellow
25 (SDD)	Red
42 (SDD)	White
67 (SDD)	Orange
109 (SDD)	Blue
176 (SDD)	Pink
200 (SDD)	Light blue

Grade UN 0500 / 1.4S (470 X 295 X 315 mm)				
Length (m)	Each/Bundle	Each/Box	Net Weight (kg)	Gross Weight (kg)
2.4	5	75	3.5	7.5
3.6	5	75	4.0	8.0
4.8	5	75	4.0	8.5
6.0	5	75	5.0	9.0
7.2	5	75	5.5	9.5
9.0	5	60	5.0	9.0
12.0	5	60	6.0	10.0
15.0	5	45	5.5	9.0
18.0	5	45	6.0	10.0
21.0	4	36	5.5	9.0
24.0	4	36	6.0	9.5
30.0	4	24	5.0	8.0

* Based on one box (UN certified)

Hazard Classification

UN No. (Class / Division):	0360 (1.1B) / 0500 (1.4S)
Proper Shipping Name	DETONATOR ASSEMBLIES, NON- ELECTRIC for blasting
EMS	F-B, S-X (1.1B / 1.4S)

Packaging

HiNEL® Plus TWINDET detonators are packed in cardboard boxes. Each box contains only a single lead length and delay.

Grade UN 0360 / 1.1B (470 X 295 X 330mm)				
Length (m)	Each/Bundle	Each/Box	Net Weight (kg)	Gross Weight (kg)
2.4	10	200	8.5	10.0
3.6	10	200	10.0	11.5
4.8	10	180	10.0	11.5
6.0	10	160	11.0	12.5
7.2	10	140	10.5	12.0
9.0	5	110	9.5	11.0
12.0	5	90	8.5	10.0
15.0	5	80	9.0	10.5
18.0	5	70	8.0	9.5
21.0	5	60	7.5	9.0
24.0	4	40	7.0	8.5
30.0	4	40	8.0	9.5

Safety

HiNEL® Plus TWINDET detonator assemblies are designed to reduce the risk of initiation by static electricity, stray electrical currents and radio wave transmissions. The surface detonator is completely enclosed within the connector block and protects against accidental initiation. As this detonator is assembled into the connector block, never attempt to disassemble in any way. As high-electrical shocks, such as lightning, may cause initiation, it is recommended that personnel evacuate to a safe distance and keep away from the blasting site. HiNEL® Plus TWINDET detonator should be isolated from energy sources including impact, heat or friction. HiNEL® Plus TWINDET Series detonators may be used in temperatures up to 70°C.

Storage

All ignition sources, such as matches and lighters, are strictly prohibited within minimum of 8 meters radius of the detonators.

HiNEL® Plus TWINDET detonators should be stored in a properly conditioned magazine of cool and dry atmosphere.

HiNEL® Plus TWINDET detonators must be used within 12 months after opening the packaging. Detonators that are older than four years should not be used.

Store in a secure magazine, access to products and storage should be restricted to authorized personnel.

Delay detonators should be used in order of manufacturing date as they deteriorate with age. Use oldest stored product first.

HiNEL® Plus- TWINDET

Revised on: July 9th, 2020 (Ver 1.4)

www.hanwhacorp.co.kr/eng/explosives

TECHNICAL DATA SHEET

HiNEL® Plus- TWINDET



Disclaimer

The information in this Technical Data Sheet is correct as of the date issued and are subject to periodic review. Hanwha reserves the right in its sole discretion and without prior written notice to modify the product(s) and/or specifications described herein ("Product"). Hanwha disclaims any warranties with respect to Product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of Product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.

The use of Product is an intrinsically dangerous activity and must be restricted to qualified and trained users in possession of any necessary permits and licenses, and comply at all times with appropriate safety and risk prevention measures and with applicable laws.

This document and any accompanying information is not intended to constitute – and shall not be construed as – an offer or contractual commitment on Hanwha's side. For further information about Hanwha Products, please contact your distributor or sales representative directly.

Please contact the following offices for any emergency or enquiry.

Head Office (Korea)

Hanwha Corporation

Hanwha Building 17th floor
86 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 04541
TEL. +82 2 729 1629
FAX. +82 2 729 1850
E-mail commercial@hanwha.com

HMS INDONESIA

PT. Hanwha Mining Services Indonesia

Talavera Office Park, Suite Area, 21th Floor
JL. TB Simatupang Kav 22 Cilandak
Barat Jakarta Selatan 12430
TEL. +62 21 2782 8378
FAX. +62 21 2782 8643
E-mail hmsindonesia@hanwha.com

HMS AUSTRALIA

Hanwha Mining Services Australia Pty Ltd

Level 9, 132 Arthur Street North Sydney NSW 2060
Australia
TEL. +61 416 770 529
Emergency 1800 054 055
E-mail australia@hanwha.com

HMS LATIN AMERICA

Hanwha Mining Services Chile

Alonso de Cordova 5870, Office 707, Las Condes,
Santiago, Chile
TEL. +56 2 2993 7546
E-mail hmschile@hanwha.com

HMS USA

Hanwha Mining Services USA

420 East South Temple Suite 260, Salt lake City
UTAH 84111, USA
TEL. +1 801 336 1553, 1602
FAX. +1 801 384 0567
E-mail leehw@hanwha.com

SOUTH AFRICA

Hanwha Corporation Johannesburg

Cedar Office estate Block 1, Unit 1A
Corner Stinkwood Cl & Cedar Rd broad acres
2021, Johannesburg, South Africa
TEL. +27 11 317 7300
FAX. +27 11 465 0499
E-mail yhlee@hanwha.com

HiNEL® Plus- TWINDET

Revised on: July 9th, 2020 (Ver 1.4)

www.hanwhacorp.co.kr/eng/explosives