

TECHNICAL DATA SHEET

NewVEX™ - Permissible Emulsion Explosives



Description

NewVEX™ is a Water in Oil (W/O) type emulsion explosive packaged in paper. NewVEX™ is mainly designed for use in underground coal mines to reduce the flame size, explosion temperature and blasting fumes. With water, heat-reducing agent, flame extinguishing agent and inert matter as its components, NewVEX™ does not cause secondary explosion such as gas or dust explosion in underground coal mines. It has excellent anti-shock properties strengthened by a physical sensitizer.

Features & Benefits



NewVEX™ is designed to prevent gas and coal dust explosion from flame using heat-reducing and flame extinguishing agents. It also emits lower level of blasting fumes with reduced level of CO and NOx as well as other harmful gases. NewVEX™ is highly resistant to impact and explosive residues even in close spacing of underground coal mines.

NewVEX™ 28mm: Permissible explosive approved for use in underground coal mines.

NewVEX™ 50mm: Relative bulk strength is about 10% greater than that of NewVEX™ 28mm. It is mainly used for blasting rocks inside underground coal mines.

Technical Data

NewVEX™	
Velocity of Detonation [VOD] (m/s) ^[A]	4,500
Density (g/cc)	1.07
Relative Weight Strength (%) ^[B]	79
Relative Bulk Strength (%) ^[B]	103
Water Resistance	Excellent
Minimum Temperature	Down to -20°C
Shelf Life	1 years

[A]: Confined @ 36mm diameter

[B]: ANFO = 100% @ 0.8g/cc, calculations with 100MPa

Packaging

NewVEX™		
Packaging	Paper Cartridge	
Diameter (mm)	28	50
Box size (mm)	420 x 335 x 220	445 x 270 x 195
Length (mm)	200	420
Weight (g/each)	125	1000
Quantity (each/box)	160	20
Net Explosive Weight (kg/box)	20	20

* The error range of weight/cartridge in the table above is within -3 to +5%

Hazard classification

Authorised Name	NewVEX™
UN No.	0241
Classification	1.1D
Proper Shipping Name	EXPLOSIVE BLASTING, TYPE E

Safety

When using NewVEX™, avoid contact with eyes or skin and wash hands thoroughly after handling. Keep NewVEX™ away from sources of heat, sparks, flame or hot surfaces and avoid mixing with combustibles or incompatible materials.

Storage

All explosives are classified as Dangerous Goods and must be stored and secured in accordance with relevant local and national regulations.

NewVEX™

Revised on : April 10th, (Ver 1.1)
www.hanwhacorp.co.kr/eng/explosives

TECHNICAL DATA SHEET

NewVEX™ - Permissible Emulsion Explosives



Disclaimer

The information in this Technical Data Sheet is correct as of the date issued and are subject to periodic review. Hanwha reserves the right in its sole discretion and without prior written notice to modify the product(s) and/or specifications described herein ("Product"). Hanwha disclaims any warranties with respect to Product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Given the variety of factors that can affect the use and application of Product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application.

The use of Product is an intrinsically dangerous activity and must be restricted to qualified and trained users in possession of any necessary permits and licenses, and comply at all times with appropriate safety and risk prevention measures and with applicable laws.

This document and any accompanying information is not intended to constitute – and shall not be construed as – an offer or contractual commitment on Hanwha's side. For further information about Hanwha Products, please contact your distributor or sales representative directly.

Please contact the following offices for any emergency or enquiry.

Head Office (Korea)

Hanwha Corporation

Hanwha Building 17th floor 86 Cheonggyecheon-ro, Jung-gu
Seoul, Korea 04541

TEL. +82 2 729 1629

FAX. +82 2 729 1850

E-mail commercial@hanwha.com

HMS INDONESIA

PT. Hanwha Mining Services Indonesia

Talavera Office Park, Suite Area, 21th Floor
JL. TB Simatupang Kav 22 Cilandak
Barat Jakarta Selatan 12430

TEL. +62 21 2782 8378

FAX. +62 21 2782 8643

E-mail hmsindonesia@hanwha.com

HMS AUSTRALIA

Hanwha Mining Services Australia Pty Ltd

Level 9, 132 Arthur Street North Sydney NSW 2060
Australia

TEL. +61 416 770 529

Emergency 1800 054 055

E-mail australia@hanwha.com

HMS LATIN AMERICA

Hanwha Mining Services Chile

Alonso de Cordova 5870, Office 707, Las Condes,
Santiago, Chile

TEL. +56 2 2993 7546

E-mail hmschile@hanwha.com

HMS USA

Hanwha Mining Services USA

420 East South Temple Suite 260, Salt lake City
UTAH 84111, USA

TEL. +1 801 336 1553, 1602

FAX. +1 801 384 0567

E-mail leehw@hanwha.com

SOUTH AFRICA

Hanwha Corporation Johannesburg

Cedar Office estate Block 1, Unit 1A
Corner Stinkwood Cl & Cedar Rd broad acres
2021, Johannesburg, South Africa

TEL. +27 11 317 7300

FAX. +27 11 465 0499

E-mail yhlee@hanwha.com

NewVEX™

Revised on : April 10th, (Ver 1.1)
www.hanwhacorp.co.kr/eng/explosives